

ARMOSCREED

Cement Based Heavy Duty Floor **Screed Plaster**

Description:

ARMOSCREED is a cement based, single component pre bagged floor screed. It consists of hydraulic cement, graded aggregates, silica, fiber and special chemical additives to provide high compressive strength screed at controlled thicknesses. ARMOSCREED is formulated to be applied in thickness from 30 mm to 100 mm. Its main function is to level uneven floor especially when high thickness is needed prior to laying subsequent floor finishing like carpet, tiles, PVC sheet, epoxy coating, rubber sport sheet, etc.

Applications:

ARMOSCREED is used at:

- Leveling old or new concrete floors.
- Leveling and smoothing concrete floors prior to laying on decorative floor coverings, carpets, floor tiles, PVC flooring, and parquet floors.
- Storage areas.
- Area with limited access.

Advantages:

- High strength for pedestrian traffic and medium loads.
- Applicable in thicknesses from 30 mm to 100 mm.
- High bonding to substrate.
- Single component, ease of application.
- Trowelable, accepts subsequent finishes; coatings, membrane, tiling etc.
- Compatible with all cementitious substrate.

Instructions for Use:

Surface Preparation:

All surfaces should be sound, clean, dry and free from loose material, efflorescence, laitance, curing compounds, dirt, oil and grease. Concrete substrate should have been placed for at least 28 days and

have moisture content less than 5%. Contamination or excessive concrete laitance can be removed by utilizing grinding, captive blasting and sand blasting. If the substrate is restricted to access, utilise preparation by handy mechanical tools. Any necessary repairs should be carried out using one of MATEX range of concrete repair products. Consult with Technical Department for recommendation.

If fully bonded screed is required, ARMOPRIME AC or SBR slurry should be applied to the concrete substrate as a bonding and priming layer. ARMOPRIME AC can be applied with a rate of 4 to 6 m²/lt. As an alternative, to prepare the slurry primer mix 1 volume of MEGABOND SBR to 1 volume of clean water with 3 volumes of fresh cement and mix until a smooth consistent slurry is prepared. Pour the mixed slurry into the concrete surface, and immediately apply ARMOSCREED mix in order to insure good adhesion with the substrate.

For un-bonded screed, primer will not be required. Concrete substrates should be soaked with clean water prior to screed application. Free water on the surface should be allowed to disperse before laying. In case of Floating screed design, place a suitable separating or damp proof membrane over the substrate before applying the screed mortar.

Mixing:

ARMOSCREED must be mixed mechanically with low speed drill mixer (200-300 rpm) fitted with suitable paddle. For large production use vessel mixer. For the preparation of mixture, pour into a container 5.5 to 6.0 liters of water, then add the 50kg bag of powder screed to the water and mix for 3 minutes until a uniform, lump free consistency mix is achieved. No further water should be added to the mix. Do not add water to the mix once its start to set.

Application:

While ARMOPRIME AC is tacky apply the mixture of ARMOSCREED to the floor directly. The floor has to be prepared by guides, and the amount of mix should

ARMOSCREED

comply with the area of application to avoid multiple casting times.

Spread evenly the mixture to the desired thickness, impact and level it carefully as ARMOSCREED is not a self-leveling product. Allow material to initially set before final touches with an aluminum float or a helicopter floating machine. After casting is completed, protect the floor from direct sunlight, high winds or rain, and cure for two days with clean water. Flooring finishing material can be applied on top of ARMOSCREED after 7 days from casting, depending on the thickness, the supports humidity and the weather conditions.

Standards:

ARMOSCREED conforms to:

- BS 1201, BS 882

TECHNICAL PROPERTIES

Color	:	Cement Grey
Compressive Strength	:	38 N / mm ²
Density	:	2.20 g/cm ³
Working time at 25°C	:	50 minutes
Open to foot traffic	:	24 hours
To receive further coats	:	14 days
To receive tiling	:	7 days
Aggregate Size	:	Up to 1.18 mm

Packaging:

ARMOSCREED is available in 50 Kg bags.

Coverage:

ARMOSCREED achieves coverage of 2.20 square meters @ 10 mm thickness.

Storage:

Store in original packing in dry conditions away from direct sunlight and high humidity levels.

Shelf Life:

ARMOSCREED can be utilized within 12 months of production date if stored in proper conditions in unopened original packing.

Cleaning:

Clean tools and equipment with water before material harden.

Remarks:

- During summer season or temperature higher than 40°C, working area should be covered to prevent the direct sun effects. Keep equipment cool and use cold water for mixing the product.
- Protect the freshly applied ARMOSCREED from direct sunlight and/or strong drying wind.
- ARMOSCREED should be cured for minimum 2 days with clean water.
- Most floor covering can be laid after 7 days.
- Do not use where negative hydrostatic pressure is evident (i.e. rising damp).

Health and Safety:

- Use goggles and gloves during application. Do not breathe vapor of products.
- Avoid contact with eyes or skin.

MATEX Rev.00-1015

This technical data sheet is not considered as local building codes. It shall be used as general reference for the product, based on our current knowledge and experience. However the company do not accept any liability arising from the use of its products as it has no direct control on how and where the product is applied.

